

Pricing List

BUDDY & BUDDY LIFT PLASMOID



Buddy Plasmoid

150 Kg capacity	€5580
200 Kg capacity	€5980



Buddy Lift Plasmoid

150 Kg capacity	€6380
200 Kg capacity	€6780

Characteristics

	Buddy Plasmoid	Buddy Lift Plasmoid
Network connection via SIM card	✓	✓
Hybrid function between wheels and tracks	✓	✓
Load lifting up to 60 cm from the ground	✗	✓

Standard Equipment Included

- 1 Fastening strap for securing the load
- 1 Standard battery pack (lead-gel base)
- 1 Battery charger (220V / 24V)

Customization Available

Color customization with your preferred RAL **€290**

Optional Accessories



24V 55Ah LITHIUM battery pack with relative battery charger

€1490



Additional battery box

€470



Customizable aluminum Ramp 200x67x8 cm

€590



Foldable aluminum Ramp 115x54x3 cm (60cm long if folded)

€390



Vehicle battery charger D/VOLTAGE CONVERTER 12V220V-150W

€235



Accessory for doors and windows

€990

Data sheet

Buddy Plasmoid

Buddy Lift Plasmoid

Maximum capacity	150 200 Kg	150 200 Kg	
Weight of the machine without battery	55 Kg	72 Kg	
Dimensions			
Max depth	591 mm	599 mm	
Overall width	579 mm	579 mm	
Height from the ground	1025 mm	1025 mm	
Height from the ground (extended)	1920 mm	1920 mm	
Loading base	Width: 455 mm Depth: 348 mm Height: 3 mm		
Electric load lifting	/	60 cm	
Travel speed of 150 kg models	47 steps/min (Adjustable via proportional joystick)		
Travel speed of 200 kg models	27 steps/min (Adjustable via proportional joystick)		
Autonomy of the Standard AGM Battery	Approximately 350 steps (for 150 kg models) Approximately 300 steps (for 200 kg models)		
Autonomy of the Premium Lithium Battery	Approximately 1200 steps (for 150 kg models) Approximately 1000 steps (for 200 kg models)		
Battery types and battery weight			
Standard AGM battery	14Ah – 24 V: 12 Kg		
Premium Lithium Battery	38Ah – 24 V: 7 Kg		
Maneuvering space on the landing	80 cm	80 cm (less when lifting the load)	
Degree of protection	IP54	IP54	
Certifications			
Direttiva 2006/42 CE	EN ISO 7010:2020	EN ISO 13849-1:2015	EN 61000-6-4:2007+A1:2011
Direttiva 2014/30/UE	EN ISO 12100:2010	EN ISO 13849-2	EN ISO 3691-5:2015/A1:2020
Direttiva 2011/65/CE	EN 60204-1:2018	EN 61000-6-2:2005+AC:2005	EN 60529:1991+A1:2000+A2:2013

Payment Methods Available

20% at order confirmation, balance before shipment/collection

Wire transfer or PayPal

Warranty

12 months on mechanical and electrical parts

6 months on the standard AGM battery

Zonzini Srl
Via Caravaggio, 8
37053 Cerea, Verona
Italy

Tel.: +39 0442 330421
Email: info@zonzini.it
PEC: zonzini.pec@pec.zonzini.it
www.zonzini.it

Cod. Fisc. e Partita IVA: IT 03550540235
R.E.A. 345531
Cod. SDI: M5UXCR1
Cap. Soc. i.v.: € 600.000,00